Concurrency: Theory, Languages and Programming

– Proofs in CCS –

Session 12 – January 22, 2003

Uwe Nestmann

EPFL-LAMP

The Scheduler Problem

- informal specification
- ***specification*** as *sequential* process expression
- ***implementation*** as *concurrent* process expression
- comparison between specification and implementaton
  - proofs using ABC
  - proofs “by hand” (very close to [§ 7.3])

- a set of n processes $P_i, 0 \leq i \leq n-1$ is to be scheduled
- P_i starts by sync'ing on a_i with the scheduler
- P_i completes by sync'ing on b_i with the scheduler

- **(1)** each P_i *must not* run two tasks at a time
- **(2)** tasks of different P_i *may* run at the same time

- a_i are required to occur cyclically (initially, 1 starts)
- for each i, a_i and b_i must occur cyclically
- **(3)** maximal "progress":
  the scheduling must permit
  any of the "buttons" to be pressed
  at any time provided (1) and (2) are not violated.

Formal Specification [Mil99, § 3.6]

$i \in \{0 \ldots, n-1\} \quad X \subseteq \{0 \ldots, n-1\}$

$\mathsf{S}_{i,X}(\vec{a}, \vec{b}) \stackrel{\text{def}}{=}$ scheduler, where i is next and every $j \in X$ is running

(* we omit the parameters in the following *)

$$\mathsf{S}_{i,X} \stackrel{\text{def}}{=} \begin{cases} \sum_{j \in X} b_j.\mathsf{S}_{i,X-j} & (i \in X) \\ \sum_{j \in X} b_j.\mathsf{S}_{i,X-j} + a_i.\mathsf{S}_{(i+1) \bmod n, X \cup i} & (i \notin X) \end{cases}$$

$$\mathsf{Scheduler}_n \stackrel{\text{def}}{=} \mathsf{S}_{0,\emptyset}$$

- draw the transition graph for $n = 2$
- show that the scheduler is never deadlocked
- what is the difference when dropping the case for $i \in X$?

$$
\begin{array}{rcl}
A(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & a.c.b.\overline{d}.A \\
\hline
A(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & a.C\langle\, a,b,c,d\,\rangle \\
C(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & c.B\langle\, a,b,c,d\,\rangle \\
B(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & b.D\langle\, a,b,c,d\,\rangle \\
D(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & \overline{d}.A\langle\, a,b,c,d\,\rangle \\
\hline
\multicolumn{3}{l}{\vec{a} := a_1 \ldots, a_n,\quad \vec{b} := b_1 \ldots, b_n\quad \vec{c} := c_1 \ldots, c_n} \\
\hline
A_i(\,\vec{a},\vec{b},\vec{c}\,) & \stackrel{\text{def}}{=} & A\langle\, a_i,b_i,c_i,c_{i\ominus_n 1}\,\rangle \\
B_i(\,\vec{a},\vec{b},\vec{c}\,) & \stackrel{\text{def}}{=} & B\langle\, a_i,b_i,c_i,c_{i\ominus_n 1}\,\rangle \\
C_i(\,\vec{a},\vec{b},\vec{c}\,) & \stackrel{\text{def}}{=} & C\langle\, a_i,b_i,c_i,c_{i\ominus_n 1}\,\rangle \\
D_i(\,\vec{a},\vec{b},\vec{c}\,) & \stackrel{\text{def}}{=} & D\langle\, a_i,b_i,c_i,c_{i\ominus_n 1}\,\rangle \\
\hline
S(\,\vec{a},\vec{b}\,) & \stackrel{\text{def}}{=} & (\boldsymbol{\nu}\vec{c})\,\big(\; A_1\langle\,\vec{a},\vec{b},\vec{c}\rangle | D_2\langle\,\vec{a},\vec{b},\vec{c}\rangle | \cdots | D_n\langle\,\vec{a},\vec{b},\vec{c}\rangle\;\big)
\end{array}
$$

Formal "Implementation" (II) [§ 7.3]

$$
\begin{array}{rcl}
A(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & a.c.(b.\overline{d}.A + \overline{d}.b.A) \\
\hline
A(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & a.C\langle\, a,b,c,d\,\rangle \\
C(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & c.E\langle\, a,b,c,d\,\rangle \\
E(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & b.D\langle\, a,b,c,d\,\rangle + \overline{d}.B\langle\, a,b,c,d\,\rangle \\
B(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & b.A\langle\, a,b,c,d\,\rangle \\
D(\,a,b,c,d\,) & \stackrel{\text{def}}{=} & \overline{d}.A\langle\, a,b,c,d\,\rangle \\
\hline
A_i & \stackrel{\text{def}}{=} & A\langle\, a,b,c_i,c_{i-1}\,\rangle \\
\ldots & & \\
S_n & \stackrel{\text{def}}{=} & (\boldsymbol{\nu}\vec{c})\,\big(\; A_1 | D_2 | \cdots | D_n\;\big)
\end{array}
$$

$$\boxed{\mathsf{Scheduler}_n \stackrel{?}{\approx} S_n}$$

- ☐ model the specification for $n = 2$
- ☐ model the wrong (!) implementation for $n = 2$
- ☐ run the ABC
- ☐ analyze the transitions systems (using `step`)
- ☐ understand the problem
  w.r.t. the formal & informal specification
- ☐ model now the correct implementation for $n = 2$
- ☐ run the ABC
- ☐ understand the bisimulation relation that ABC has generated
- ☐ if time left, try out for $n = 3 \ldots$

Proofs "by Hand" (I)

means: "guessing" a bisimulation relation !

- ☐ draw the transition graph of S for $n = 2$
- ☐ generalize for greater $n \ldots$
- ☐ Observe: every reachable state is of the form

$$(\boldsymbol{\nu}\vec{c})\ (\ Q_1|Q_2|\cdots|Q_n\ )$$

  where Q is one of A, B, C, D, E.
- ☐ Observe that in any state reachable from S_n
  only one of the Q is one of A, B, C,
  while **all other** Q are either of D, E.
- ☐ analyze the "meaning" of the those states

analyze the “meaning” of the following states for $n = 4$

$$(\boldsymbol{\nu}\vec{c})\ (\ D_1|E_2|A_3|E_n\ )$$

$$(\boldsymbol{\nu}\vec{c})\ (\ E_1|D_2|C_3|E_n\ )$$

Proofs “by Hand” (III)

Let $\{i\}, Y, Z$ be any partition of $\{0 \ldots, n-1\}$.

$$A_{i,Y,Z} \stackrel{\text{def}}{=} (\boldsymbol{\nu}\vec{c})\ (\ A_i \mid \prod_{j\in Y} D_j \mid \prod_{k\in Z} E_k\ )$$

$$B_{i,Y,Z} \stackrel{\text{def}}{=} (\boldsymbol{\nu}\vec{c})\ (\ B_i \mid \prod_{j\in Y} D_j \mid \prod_{k\in Z} E_k\ )$$

$$C_{i,Y,Z} \stackrel{\text{def}}{=} (\boldsymbol{\nu}\vec{c})\ (\ C_i \mid \prod_{j\in Y} D_j \mid \prod_{k\in Z} E_k\ )$$

Note that $S_n = A_{0,\{1\ldots,n-1\},\emptyset}$.

Using the Expansion Law, we show that:

$$A_{i,Y,Z} \sim a_i.C_{i,Y,Z} + \sum_{k \in Z} b_k.A_{i,Y \oplus k, Z \ominus k}$$

$$B_{i,Y,Z} \sim b_i.A_{i,Y,Z} + \sum_{k \in Z} b_k.A_{i,Y \oplus k, Z \ominus k}$$

$$C_{i,Y,Z} \sim \sum_{k \in Z} b_k.A_{i,Y \oplus k, Z \ominus k} + + \begin{cases} \tau.A_{i+1,Y \ominus (i+1), Z \oplus i} & \text{if } i{+}1 \in X \\ \tau.B_{i+1,Y,Z \ominus (i+1) \oplus i} & \text{if } i{+}1 \in Y \end{cases}$$

Proofs "by Hand" (V)

Let $\mathcal{R}$ be the relation containing the following pairs:

$$A_{i,Y,Z} \quad , \quad \mathsf{S}_{i,Z}$$

$$B_{i,Y,Z} \quad , \quad \mathsf{S}_{i,Z \oplus i}$$

$$C_{i,Y,Z} \quad , \quad \mathsf{S}_{i+1,Z \oplus i}$$

- ☐ $\mathcal{R}$ is a weak bisimulation (up to $\sim$).
- ☐ $\mathcal{R}$ contains the pair $(S_n, \mathsf{Scheduler}_n)$.
- ☐ Q.E.D.