Concurrency: Theory, Languages and Programming

– Encoding FP in Lambda Calculus –

Session 3 – Nov 05, 2002

Martin Odersky

EPFL-LAMP

Program Equivalence

- **Question:** When are two lambda terms M and N equivalent, in the following sense:
- Exchanging M by N in a program does not change the behavior of the program
- This notion is called *operational equivalence*, written $M \cong N$.
- It is formalized as follows.

$$M \cong N \quad \text{iff} \quad \forall C.C[M] \Downarrow \quad \Leftrightarrow \quad C[N] \Downarrow .$$

- Here, $M \Downarrow$ means that evaluation of M terminates.
- Formally, $M \Downarrow$ iff $\exists V.M \twoheadrightarrow V$.

Operational Equivalence and β-Conversio

- β-Reduction also gives rise to another program equivalence, called *convertibility*.
- Define: $M =_\beta N$ iff $\exists M'.M \twoheadrightarrow M' \wedge N \twoheadrightarrow M'$.
- Then $=_\beta$ is the smallest congruence that includes reduction $\rightarrow$.
- Also, we have that: $M =_\beta N \Rightarrow M \cong N$
- **Question:** : Name two terms M, N such that $M \cong N$ but not $M =_\beta N$?

Church Encodings

- The treatment so far covered *pure* lambda calculus which consists of just functions and their applications.
- Actual programming languages add to this primitive data types and their operations, named value and function definitions, and much more.
- We can model these constructs by extending the basic calculus.
- But it is also possible to *encode* these constructs in the basic calculus itself.
- These encodings will be presented in the following.
- We will assume in general call-by-name evaluation, but will also work out modifications needed for call-by-value.

Encoding of Booleans

- An abstract type of booleans is given by the two constants *true* and *false* as well as the conditional ***if***.
- Other constructs can be written in terms of these primitives. E.g.

$$
\begin{aligned}
\textit{not } x &= \textbf{\textit{if}}\ (x)\ \textit{false}\ \textbf{\textit{else}}\ \textit{true} \\
x \mid\mid y &= \textbf{\textit{if}}\ (x)\ \textit{true}\ \textbf{\textit{else}}\ y \\
x \mathbin{\&\&} y &= \textbf{\textit{if}}\ (x)\ y\ \textbf{\textit{else}}\ \textit{false}
\end{aligned}
$$

- **Idea:** : The encoding of a boolean value $B \in \{\textit{true}, \textit{false}\}$ is the binary function

$$\lambda x.\lambda y.\ \textbf{\textit{if}}\ (B)\ x\ \textbf{\textit{else}}\ y$$

That is:

$$
\begin{array}{lcl}
\mathit{true} & \stackrel{\text{def}}{\equiv} & \lambda x.\ \lambda y.\ x \\
\mathit{false} & \stackrel{\text{def}}{\equiv} & \lambda x.\ \lambda y.\ y \\
\textbf{\textit{if}}\ c\ x\ y & \stackrel{\text{def}}{\equiv} & c\ x\ y
\end{array}
$$

Example:

$$
\begin{array}{lcl}
\textbf{\textit{if}}\ (\mathit{true})\ D\ \textbf{\textit{else}}\ E & \stackrel{\text{def}}{\equiv} & \mathit{true}\ D\ E \\
 & \stackrel{\text{def}}{\equiv} & (\lambda x\ .\lambda y.\ x)\ D\ E \\
 & \rightarrow & (\lambda y\ .\ D)\ E \\
 & \rightarrow & D
\end{array}
$$

Question: What changes to this encoding are necessary if the evaluation strategy is call-by-value?

Encoding of Lists

The encoding of Booleans can be generalized to arbitrary algebraic data types.
Example: Consider the type of lists (as defined in Haskell):

$$\textit{data List a} = \textit{Nil} \mid \textit{Cons a}\ (\textit{List a})$$

This defines a type of lists with (nullary) constructor *Nil* and (curried binary) constructor *Cons*.
A list *xs* can be accessed using a case-expression

$$\textbf{\textit{case}}\ \textit{xs of Nil}\ Arrow\ E_1 \mid \textit{Cons x xs} \Rightarrow E_2$$

Here, the expression of the second branch, E_2, can refer to the variables *x* and *xs* defined in the *Cons* pattern.

All other functions over lists can be written in terms of the case-expression.
For instance, function *car* which equals *head* except that it avoids errors, can be written as:

$$
\begin{array}{l}
car\ xs = \\
\quad \textbf{\textit{case}}\ xs\ of \\
\quad\quad Nil \qquad\qquad \Rightarrow Nil \\
\quad\ \mid\ Cons\ y\ ys \quad \Rightarrow x
\end{array}
$$

Question: How can lists be encoded?
Same principle as before: Equate a list with the case-expression that accesses it.

$$xs \stackrel{\text{def}}{\equiv} \lambda a.\lambda b.\textbf{\textit{case}}\ xs\ of\ Nil \Rightarrow a \mid Cons\ x\ xs \Rightarrow b\ x\ xs$$

That is:

$$\mathit{Nil} \stackrel{\text{def}}{\equiv} \lambda a.\lambda b.\ a$$

$$\mathit{Cons}\ x\ xs \stackrel{\text{def}}{\equiv} \lambda a.\lambda b.\ b\ x\ xs$$

or, equivalently:

$$\mathit{Cons} \stackrel{\text{def}}{\equiv} \lambda x.\lambda xs.\lambda a.\lambda b.\ b\ x\ xs$$

The pattern-bound names *x* and *xs* are now passed as parameters to the case branch that accesses them.
Example: : *car* is coded as follows:

$$\mathit{car} \stackrel{\text{def}}{\equiv} \lambda xs.\ xs\ \mathit{Nil}\ (\lambda y.\lambda ys.y)$$

Exercise: Church-encode function *isEmpty* which returns true iff the given list is empty.

Encoding of Numbers

The encoding for lists generalizes to arbitrary data types which are defined in terms of a finite number of constructors.
For instance, whole numbers don't present any new difficulties.
To see this, note that natural numbers can be coded as algebraic data types as follows:

$$\mathit{data\ Nat} \ = \ \mathit{Zero} \ \Big| \ \mathit{Succ\ Nat}$$

Hence:

$$\begin{aligned} \mathit{Zero} &\stackrel{\text{def}}{\equiv} \lambda a.\lambda b.a \\ \mathit{Succ}\ x &\stackrel{\text{def}}{\equiv} \lambda a.\lambda b.b\ x \end{aligned}$$

Note: Church encodings do not reflect types. In fact *Zero*, *Nil*, and *true* are all mapped to the same term!

Encoding of Definitions

A non-recursive value definition ***val*** $x = D\ ;\ E$ can be encoded as:

$$\textbf{\textit{val}}\ x = D\ ;\ E \quad \stackrel{\text{def}}{\equiv} \quad (\lambda x.E)\ D$$

Caveat: With a call-by-name strategy, D might be evaluated more than once.
Let's try an analogous principle for function definitions:

$$\begin{aligned} \textbf{\textit{def}}\ f\ x = D\ ;\ E \quad &\stackrel{\text{def}}{\equiv} \quad \textbf{\textit{val}}\ f = \lambda x.D\ ;\ E \\ &\stackrel{\text{def}}{\equiv} \quad (\lambda f.E)\ (\lambda x.D) \end{aligned}$$

But this fails if f is used recursively in D! (Why?)

Fixed Points to the Rescue

If we have a recursive definition of

val *f* = *E*

where *E* refers to *f*, we can interpret this as a solution to the equation

$$f \quad = \quad E$$

Another way to characterize solutions to this equation is to say that these solutions are fixed points of the function $\lambda f.E$.

Definition: A *fixed point* of a function f is a value x such that

$$f\ x \quad = \quad x$$

Proposition: The solutions of $f = E$ are exactly the fixed points of $\lambda f.E$

Proof: F is a solution of the equation

$$f = E$$

iff

$$F = [F/f]E$$

iff

$$F = (\lambda f.E)\ F$$

iff F is a fixed point of $\lambda f.E$.

Fixed Point Operators

Let's assume the existence of a *fixed point operator* Y. For every function f, $Y\,f$ evaluates to a fixed point of f. That is,

$$Y\,f \;=\; f\;(Y\,f)$$

Then we can encode potentially recursive definitions as follows:

$$\begin{aligned} \textbf{\textit{def}}\ f\ x = D\ ;\ E \quad &\stackrel{\text{def}}{\equiv} \quad \textbf{\textit{val}}\ f = Y\ (\lambda f.\lambda x.D)\ ;\ E \\ &\stackrel{\text{def}}{\equiv} \quad (\lambda f.E)\ (Y\ (\lambda f.\lambda x.D)) \end{aligned}$$

Remains the question whether Y exists.

Proposition: Let

$$Y \stackrel{\text{def}}{\equiv} \lambda f.(\lambda x.f\,(x\,x))\,(\lambda x.f\,(x\,x))$$

Then Y is a fixed point operator:

$$Y f = f\,(Y f)$$

Proof: By repeated β-reduction.

Least Fixed Points

In fact, an equation will in general have several solutions, and a function will in general have several fixed points.

Example: The equation $f = f$
has every λ-term as a solution.
Can we characterize the fixed point computed by Y?

Proposition: Among all the fixed points of a function f, Yf will return the one which diverges most often. This is also called the *least fixed point* of the function f.

Exercise: Find the least fixed point of $\lambda f.f$ (which is also the least solution of the equation $f = f$).

Connection to Domain Theory

- The definition of least fixed points is made precise in the field of *domain theory*.
- Domain theory gives λ-terms meaning by mapping them to mathematical functions.
- Divergent terms are modeled by a value $\perp$, which stands for "undefined".
- Domain theory introduces a partial ordering on values which makes $\perp$ smaller than any defined value.
- The fixed points computed by Y are the smallest with respect to this ordering.

Summary

- We have seen the basic theory of λ-calculus, and how it can express functional programming.
- Two main variants: Call-by-value and call-by-name.
- In each case, evaluation is described by reduction of function applications, using rule β (or β_V).
- λ-calculus has two important properties, which make it well suited as a basis of deterministic programming languages:
  - **Confluence:** Every term can be reduced to at most one value.
  - **Standardization:** There exists a deterministic reduction strategy which always reduces a term to a value, provided it can be done at all.

Outlook

- λ-calculus is ideally suited as a basis for functional programming.
- But it is less well suited as basis for imperative programming with side effects (essentially, need to introduce and carry along a data structure describing global state).
- It is not suitable at all as a basis for reactive systems with concurrent evaluation.
- Two new issues:
  - **Non-determinism:** If programs can have several behaviors, confluence no longer holds.
  - **Non-termination:** Operational equivalence needs to be adapted for programs that do not terminate.