Concurrency: Theory, Languages and Programming

– From CCS to PiLib –

Session 5 – November 20, 2002

Martin Odersky

EPFL-LAMP

Pilib

- Pilib is a library, which allows one to use CCS primitives in a Scala program.
- CCS constructs are modelled as Scala functions.
- Their implementation is based on Java's threads.
- Pilib's functions are implemented in two modules:
  - *concurrency* for general thread management.
  - *pilib* for CCS actions and sums.

Here is a two-place buffer implementation using Pilib.

```
import concurrency;   // make available Pilib functions
import pilib;         // without qualification.

module bufferExample with {
  def Buffer[a](in: Chan[a], out: Chan[a]): Unit = {
    def B0: Unit = { val x = in.read; B1(x) }
    def B1(x: a): Unit = choice {
        out(x) * (B0) +
        in * (y ⇒ B2(x, y))
      }
    def B2(x: a, y: a): Unit = { out.write(x); B1(y) }
    B0  // initial state
  }
}
```


Explanations

- *Chan* is the type of CCS names (or: channels).
- *Chan* takes a *type parameter* *a*, which determines the type of values that can be read from and written to the channel.
- The *Buffer* process is modelled by a recrusive Scala function, nested functions *B0*, *B1*, *B2*.
- Each nested function represents a buffer state (0 = empty, 1 = half full, 2 = full).

A Buffer Unit

```
val random = new java.util.Random();
def Producer(n: Int, l: Chan[String]): Unit = {
  sleep(1 + random.nextInt(1000));
  l.write("object " + n);
  System.out.println("Producer gave " + n);
  Producer(n + 1, l)
}
def Consumer(r: Chan[String]): Unit = {
  sleep(1 + random.nextInt(1000));
  val a = r.read;
  System.out.println("Consummer took " + a);
  Consumer(r)
}
```



```
def main(args: Array[String]): Unit = {
  val in = new Chan[String];
  val out = new Chan[String];
  spawn < Producer(0, in) | Consumer(out) | Buffer(in, out) >
}
```

Action prefix	π	::=	$x(y)$	receive y along x
		|	$\bar{x}\langle y\rangle$	send y along x
Guarded process	G	::=	$\pi.P$	
Process	P	::=	$\sum_i G_i$	summation
		|	$P_1 \mid P_2$	composition
		|	$\nu a.P$	restriction
		|	$A\langle x_1, ..., x_n\rangle$	agent
Agent definition	D	::=	$A(x_1, ..., x_n) = P$	
Term	t	::=	$D_1, ..., D_n \vdash P$	

From CCS to Pilib

Guarded process

$[\![x(y).P]\!]$	=	x * (y => $[\![P]\!]$)
$[\![\bar{x}\langle v\rangle.P]\!]$	=	$x(v)$ * ($[\![P]\!]$)

Process

$[\![\pi_1.P_1 + ... + \pi_n.P_n]\!]$	=	choice ($[\![\pi_1.P_1]\!]$ + ... + $[\![\pi_n.P_n]\!]$)
$[\![P_1 \mid \ldots \mid P_n]\!]$	=	spawn < $[\![P_1]\!]$ | ... | $[\![P_n]\!]$ >
$[\![\nu a.P]\!]$	=	{ val a = new Chan[T]; $[\![P]\!]$ }
$[\![A\langle x_1, ..., x_n\rangle]\!]$	=	$A(x_1, ..., x_n)$

Agent definition

$[\![A(x_1, ..., x_n) = P]\!]$	=	def A(x_1: T, ..., x_n: T): Unit = $[\![P]\!]$